

Smart business solution

The Ricoh IM 600SRF is an intelligent and always current device. Cloud enabled, it will adapt seamlessly to your changing business needs.

Cloud-enabled 4-in-1 MFP:

- Print, copy, scan & fax
- Single-pass scanning
- Internal staple finisher
- Regular firmware upgrades

This versatile 4-in-1 MFP can print, copy, scan and fax. It is also Cloud enabled. Using the integral SPDF (Single Pass Document Feeder), double sided originals can be scanned in a single pass and uploaded to Cloud-share services, such as DropBox™ and Sharepoint™. The IM 600SRF also features a compact internal finisher, which neatly collates and staples document sets.

Super-sized Smart Operation Panel:

- Intuitive user interface
- Time-saving Smart apps
- Secured authentication
- Ricoh Smart Integration



Effortlessly productive, this Letter/A4 black and white MFP will meet the most demanding high speed / high volume requirements. To improve workflow speed, the first immaculate 1,200 dpi print is ready in 6 seconds and multipage document sets are delivered at a highly productive 60ppm (A4)/62ppm (Letter). With its long-life imaging drum offering maintenance free performance, reliability is a given — and with stacks of paper on line and the MFP switching seamlessly between trays, there is seldom any need to stop.

Ricoh's Smart Operation Panel empowers users. Employees can connect seamlessly to the MFP and print from / scan to smartphones and tablets. Confidential documents can be password protected and held pending release, while tap and go authentication helps protect information security. The Smart Operation Panel also supports workflow solutions, such as Streamline NX or Ricoh Smart Integration, which can help automate your document workflow processes.

Productive and reliable performance:

- 1,200 dpi resolution
- Fast 60ppm (A4)/62ppm (Letter) throughput
- Up to 2,600 sheet paper capacity
- Maintenance-free to 500k*



* Based on 3 pages per job

RICOH IM 600SRF

MAIN SPECIFICATIONS

GENERAL

Warm-up time 25.4 seconds First output speed: B/W Less than 6 seconds Continuous output speed 60ppm (A4)/62ppm (Letter)

2 GB Memory: standard 2 GB Memory: maximum HDD: standard 320 GB HDD: maximum 320 GB SPDF capacity 100 sheets 88.2 lbs. (40 kg) Weight

18.9" x 21.4" x 29.1" (480 x 543 x 740 mm) Dimensions: W x D x H

120 - 127V 60Hz Power source

COPIER (STANDARD)

Multiple copying Up to 999 copies 600 x 600 dpi Copy resolution: maximum 65% to 155% Enlargement/reduction

From 25% to 400% in 1% steps

PRINTER (STANDARD)

CPU Intel® Apollo Lake Processor 1.3 GHz

PCL5e, PCL6(XL), PostScript 3 (emulation), PDF direct (emulation) Printer language: standard

Genuine Adobe® PostScript® 3™ Printer language: option Print resolution: maximum 1,200 x 1,200/1 bit

WEP, WPA, WPA2

Standard interfaces Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host Type miniB, USB Host I/F, USB Device 2.0, SD Card Slot, NFC tag, Bluetooth

Wireless LAN (IEEE 802.11a/b/g/n), USB Device Server Option Network interface: option

Apple AirPrint™, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector Mobile printing capability

Network protocol TCP/IP (IP v4, IP v6)

Windows® environments Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008/R2, Windows® Server 2012/R2, Windows® Server 2016, Windows® Server 2019

Mac OS environments Macintosh OS X Native v10.11 or later

UNIX environments UNIX Sun® Solaris (10), HP-UX (11.x, 11i v2, 11i v3), SCO Open Server (5.0.7, 6.0, 6.x), RedHat® Linux Enterprise (V4, V5, V6), IBM® AIX (V6.1, V7.1, V7.2)

SAP[®] R/3[®] SAP® environments

SCANNER (STANDARD)

Scanning: B/W 60 ipm A4, 62 ipm Letter (300 dpi) Simplex; 100 ipm A4, 102 ipm Letter (300 dpi) Duplex Scanning: full color 40 ipm A4, 42 ipm Letter (300 dpi) Simplex; 62 ipm A4, 64 ipm Letter (300 dpi) Duplex

Resolution: maximum 600 dpi (up to 1200 dpi via TWAIN)

Compression method BW (TIFF (MH, MR, MMR, JBIG2), Grayscale), Color (JPEG) Single page: TIFF, JPEG, PDF, High compression PDF, PDF/A File formats Multi page: TIFF, PDF, High compression PDF, PDF/A

E-mail, Folder, USB, SD Card Scan modes

FACSIMILE (STANDARD)

Circuit/Compatibility PSTN. PBX/ITU-T (CCITT) G3

Transmission speed 2 seconds Modem speed: maximum 33.6 Kbps

Resolution: standard 8x7.7 line/mm, 200 x 200 dpi MH, MR, MMR, JBIG Compression method

Scanning speed 61 spm A4, 62 spm Letter (300 dpi) Simplex

Page memory size Standard: 4 MB

With optional SAF memory: 8 MB

SAF memory size Standard: 4 MB (approximately 320 pages)

Optional: 60 MB (approximately 4,800 pages)

RICOH IM 600SRF

MAIN SPECIFICATIONS

PAPER HANDLING

A4, A5, A6, B5, B6, Legal, Letter, HLT, Executive Recommended paper size 500 sheets Paper input: standard Paper input: maximum 2,600 sheets Paper output: standard Exit Tray: 250 sheets; Finisher Tray: 250 sheets; Total: 500 sheets Trays: (64 - 120 g/m²), Bypass: (60 - 220 g/m²), Duplex: (64 - 120 g/m²) Paper weight Paper types Plain, Recycle, Special, Color, Letterhead, Preprinted, Bond, Envelopes, Label & OHP





















FCOLOGY

Power consumption: maximum Less than 1,500 W 805 W Power consumption: operation Power consumption: ready 94 1 W 0.6 W Power consumption: sleep TEC 3.3 kWh Environmental standard ENERGY STAR® EPEAT[®] Silver Rated*

FINISHER (STANDARD)

1 x 250-sheet Internal Finisher Stack capacity: 250 sheets Staple capacity: 50 sheets A4, Letter or smaller; 30 sheets Legal or length above 300mm, 11.8" Staple paper size: A4, B5, Legal, Letter, Executive Staple paper weight: 60 - 90 g/m² Staple position: Top

*EPEAT Silver rating is applicable only in the USA.

PAPER HANDLING OPTIONS

Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Legal, Letter, HLT, Executive, Envelopes; Paper weight: 64-120 g/m² 1 x 500-sheet Paper Feed Unit (PB 1160) $\ensuremath{^{\star}}$ A maximum of four paper trays can be installed on the device.

OTHER OPTIONS

Caster Table Type M40, VM Card Type M37, Device Server Option Type M37, File Format Converter Type M19, OCR Unit Type M13, NFC Card Reader Type M24, PostScript3 Unit Type M40, IPDS Unit Type M40, Medium Cabinet Type T, Tall Cabinet Type U, IEEE 802.11 Interface Unit Type M24, FAX Memory Unit Type M19 64MB, Optional Counter Interface Unit Type M12, ESP XG-PCS-15D, ESP S1 Power Filter

CONSUMABLES

Starter toner	11,000 prints
Toner: regular yield	25,500 prints
Toner: high yield	40,000 prints
Feed Roller MP 601 (Std. Tray)	500,000 prints
Feed Roller MP 601PB (Optional Tray)	500,000 prints
Staple Set	5,000 staples
Staple Refill	10,000 staples
Consumable yield measuring method ISO/IEC 19752	

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

70 Valley Stream Parkway Malvern, PA 19355



1-800-63-RICOH



www.ricoh-usa.com

