

Highly intelligent device

Intelligent, productive and utterly reliable, this compact Letter/A4 black and white multifunction printer effortlessly keeps pace with your changing business requirements.

Intuitive touchscreen interface:

- Smart Operation Panel
- Time-saving Smart apps
- Ricoh Smart Integration
- Regular firmware upgrades

The IM 550F can print, copy, scan and fax. Its 10.1 inch Smart Operation Panel simplifies operation. Smart apps — such as ID Card Copy or Cloud apps leveraging Ricoh Smart Integration — can automate time-consuming processes. And with RICOH Always Current Technology, you will always have access to the latest features.

Productive print performance:

- Fast single-pass scanning
- Fast 55/57 (A4/Letter) print speed
- Maximum 2,600-sheet paper capacity
- Long-life 500k drum*



The versatile 4-in-1 MFP is equipped with a Single Pass Document Feeder (SPDF). To save time, double sided originals are scanned in a single pass and can be forwarded to email or uploaded directly to Cloud-share services, such as DropBox™ and Sharepoint™. The Smart Operation Panel also supports the use of enterprise workflow solutions, including Ricoh's Streamline NX. And, with Near Field Communication (NFC), secured authentication is as easy as tap and go.

Enterprise-level security:

- Upload directly to Cloud
- Run enterprise solutions
- Secured authentication

Driving your business forward, the IM 550F powers quickly through workgroup print requirements. Its Intel processor effortlessly handles PCL and PostScript files. To improve workflow speed, the first immaculate 1,200 dpi print is ready in 7 seconds and multipage document sets are delivered at a productive 55 (A4)/57 (Letter) ppm. What is more, with up to 2,600 sheets of paper on line and a long-life imaging drum ensuring maintenance free performance, there is seldom any need for it to stop.



^{*} Based on 3 pages per job

RICOH IM 550F

MAIN SPECIFICATIONS

GENERAL

Warm-up time Standard Mode: 60 seconds ; Quick Mode: 25.4 seconds

First output speed: B/W 6 seconds

Continuous output speed 55ppm (A4) / 57ppm (Letter)

 Memory: standard
 2 GB

 Memory: maximum
 2 GB

 HDD: standard
 320 GB

 SPDF capacity
 100 sheets

 Weight
 63.9 lbs. (29 kg)

Dimensions: W x D x H 18.9" x 21.2" x 25.4" (480 x 539 x 644 mm)

Power source 120 - 127V 60Hz

COPIER (STANDARD)

 First copy speed
 7 seconds

 Multiple copying
 Up to 999 copies

 Resolution
 600 x 600 dpi

Enlargement/reduction 65% to 155% (Available presets: 65%, 78%, 93%, 100%, 129% and 155%)

Zoom From 25% to 400% in 1% steps

PRINTER (STANDARD)

CPU Intel® Apollo Lake Processor 1.3 GHz

Printer language: standard PCL5e, PCL6(XL), PostScript 3 (emulation), PDF direct (emulation)

Printer language: option Genuine Adobe® PostScript®3™

Print resolution: maximum 1,200 x 1,200/1 bit

Security WEP, WPA, WPA2

Standard interfaces Ethernet 10 base-T/100 base-T, USB Host Type miniB, USB Host I/F, USB Device 2.0, SD Card Slot, NFC tag, Bluetooth

Network interface: option Wireless LAN (IEEE 802.11a/b/g/n), USB Device Server Option

Mobile printing capability Apple AirPrint™, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector

Network protocol TCP/IP (IP v4, IP v6)

Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2012/R2, Windows® Server 2012/R2, Windows® Server 2016, Windows® Server 2019

Mac OS environments Macintosh OS X Native v10.11 or later

UNIX environments UNIX Sun® Solaris (10), HP-UX (11.x, 11i v2, 11i v3), SCO Open Server (5.0.7, 6.0, 6.x), RedHat® Linux Enterprise (V4, V5, V6), IBM® AIX (V6.1, V7.1, V7.2)

SAP® environments SAP® R/3®

SCANNER (STANDARD)

Scanning: B/W 60 ipm A4, 62 ipm Letter (300 dpi) Simplex; 100 ipm A4, 102 ipm Letter (300 dpi) Duplex
Scanning: full color 40 ipm A4, 42 ipm Letter (300 dpi) Simplex; 62 ipm A4, 64 ipm Letter (300 dpi) Duplex

Resolution: maximum 600 dpi (up to 1200 dpi via TWAIN)

Compression method

BW (TIFF (MH, MR, MMR, JBIG2), Grayscale), Color (JPEG)

File formats

Single page: TIFF, JPEG, PDF, High compression PDF, PDF/A

Multi page: TIFF, PDF, High compression PDF, PDF/A

Scan modes E-mail, Folder, USB, SD Card

FACSIMILE (STANDARD)

Circuit/Compatibility PSTN, PBX/ITU-T (CCITT) G3

Transmission speed 2 seconds
Modern speed: maximum 33.6 Kbps

Resolution: standard 8x7.7 line/mm, 200 x 200 dpi Compression method MH, MR, MMR, JBIG

Scanning speed 61 spm A4, 62 spm Letter (300 dpi) Simplex

Page memory size Standard: 4 MB

With optional SAF memory: 8 MB

SAF memory size Standard: 4 MB (approximately 320 pages)
Optional: 60 MB (approximately 4,800 pages)

RICOH IM 550F

MAIN SPECIFICATIONS

PAPER HANDLING

 Recommended paper size
 A4, A5, A6, B5, B6, Legal, Letter, HLT, Executive

 Paper input: maximum
 2,600 sheets

 Paper output: standard
 500 sheets

 Paper weight
 Trays: (64 - 120 g/m²), Bypass: (60 - 220 g/m²), Duplex: (64 - 120 g/m²)

 Paper types
 Plain, Recycle, Special, Color, Letterhead, Preprinted, Bond, Envelopes, Label & OHP





















ECOLOGY

Power consumption: maximum

Power consumption: operation

760 W

Power consumption: ready

87.4 W

Power consumption: sleep

0.6 W

TEC

2.9 kWh

Environmental standard

ENERGY STAR®

EPEAT® Silver Rated*

PAPER HANDLING OPTIONS

1 x 500-sheet Paper Feed Unit (PB 1160) Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Legal, Letter, HLT, Executive, Envelopes; Paper weight: 64 - 120 g/m²
*A maximum of four paper trays can be installed on the device.

*EPEAT Silver rating is applicable only in the USA

OTHER OPTIONS

Caster Table Type M40, VM. CARD Type M37, Device Server Option Type M37, File Format Converter Type M19, OCR Unit Type M13, NFC Card Reader Type M24, PostScript3 Unit Type M40, IPDS Unit Type M40, Medium Cabinet Type T, Tall Cabinet Type U, FAX Memory Unit Type M19 64MB, IEEE 802.11 Interface Unit Type M24, Optional Counter Interface Unit Type M12, ESP XG-PCS-15D, ESP S1 Power Filter

CONSUMABLES

 Starter toner
 10,000 prints

 Toner: regular yield
 25,500 prints

 Feed Roller MP 601 (Std. Tray)
 500,000 prints

 Feed Roller MP 601PB (Optional Tray)
 500,000 prints

 Consumable yield measuring method ISO/IEC 19752
 19752

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and

supplies. Some features may require additional options and/or charges.

Ricoh Latin America



Certified ISO 9001
Certified ISO 14001



Ricoh Latin Americ

©2019. Rich Latin America. All rights reserved. Ricch® and the Ricch logo are registered trademarks of Ricch Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricch products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricch makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricch products and services are as set forth in the express warranty statements accompanying them.